

The basic epoxy mortar for applications in concrete







Crash barriers and sound insulation walls

BUILDING MATERIALS

- Approved for anchorings in:
- Concrete C20/25, cracked and noncracked



ASSESSMENT/APPROVAL



VCLC

ADVANTAGES

- FIS EB is approved for use in cracked concrete and for rebar applications and achieves a good performance in these applications which enables an economical use of injection mortar.
- Variable anchorage depths from 4xd to 20xd allow for ideal adaptation to the load to be applied.
- FIS EB can be used in various conditions (dry/wet concrete, flooded hole), thus working in almost all situations on the building site and making it a safe and reliable system.

APPLICATIONS

- Heavy steel constructions
- ConsolesSilo installations
- Tall shelving
- post-installed rebar connections

SNABLINE COM

СНАБЖЕНИЕ КОМПАНИЙ

FUNCTIONING

- The epoxy mortar FIS EB combined with the threaded rod FIS A is suitable for pre-positioned and push-through installation.
- Resin and hardener are stored in two separate chambers and are not mixed and activated until extrusion through the injection capsule in the static mixer.
- The mortar is injected bubble-free from the drill hole base.
- The mortar bonds the entire surface of the anchor rod with the drill hole wall and seals off the drill hole.
- The anchor rod is set manually by slightly rotating it until it reached the drill hole base.
- During push-through installation, the annular gap between the anchor rod and the attachment is filled with FIS EB.

FOR USE WITH

Accessories for concrete: threaded rod FIS A see page 152

122



TECHNICAL DATA



Epoxy mortar **FIS EB**

FIS MR

		Approval	Languages on the cartridge	Scale unit	Contents	Sales unit
Item	ArtNo.	ETA				[pcs]
FIS EB 390 S	534984		GB, E, P	180	1 cartridge 390 ml, 2 x FIS MR	6
FIS EB 390 S	534985		TR, RUS, KR	180	1 cartridge 390 ml, 2 x FIS MR	6
FIS EB 585 S	534986		GB, E, P	270	1 cartridge 585 ml + 2 x FIS UMR	6
FIS MR	096448	-	_	_	10 static mixer	10

ACCESSORIES DRILL HOLE CLEANING

Cleaning brush BS

		Brush diameter	For drill diameter	Sales unit
Item	ArtNo.	[mm]	[mm]	[pcs]
BS ø 12	078179	13	12	1
BS ø 14	078180	16	14	1
BSø16/18	078181	20	16/18	1
BS ø 24	078182	26	24	1
BS ø 25	097806	27	25	1
BS ø 28	078183	30	28	1
BS ø 35	078184	40	30/32/35	1

- Cleaning brush with thread M 8

SDS-Adapter M8

		Brush diameter	For drill diameter	Sales unit
Item	ArtNo.	[mm]	[mm]	[pcs]
Brush for drill-Ø 40 mm	505061	42	40	1
Brush for drill-Ø 45 mm	506254	47	45	1
Brush for drill-Ø 55 mm	505062	58	55	1
FIS brush extension	508791	-	_	1
SDS Chuck	530332	_	_	1



Compressed-air cleaning tool ABP

		Match	Sales unit
Item	ArtNo.		[pcs]
Compressed-air cleaning tool ABP	059456	FIS A M 16 - M 30	1

